

Mipa Linienmarkierer Profi

Item no 68210 + Colour no

Technical data sheet

mipa

page 1 / 2 Professional Coating Systems

Intended use

Mipa Linienmarkierer Profi is a fast-drying special paint for professional use. The excellent adhesion provides a durable and hard wearing line mark. Superior coverage and sharp edges can be achieved in conjunction with our line marking trolleys "Allround" and "Standard". Especially suitable for the marking and line marking of car parks, in the private sector as well as for safety markings in the industry.

Processing conditions



Substrates

Stone, concrete, etc.
Also suitable for absorbent and damp substrates.

Pre-treatment / cleansing

If possible, the substrate should be clean and free of grease.

Characteristics

Highly opaque, fast-drying quality
For permanent markings (durability of the marking depends on the substrate, location: e.g. indoors or outdoors, the daily stress, etc.)
Highly resistant to abrasion

Colour / gloss level

White, traffic yellow, traffic blue, traffic red, traffic green / matt



Preparation

Before use, shake can vigorously for 1 - 2 min!




Do not subject the can to high mechanical stress!



Application

Spray to test - spray distance approx. 20 - 30 cm



Flash-off time

-



After use

Self-cleaning system, therefore the spray can can be emptied 100 %.

Version: en 0126

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00 · mipa@mipa-paints.com · www.mipa-paints.com


Mipa Linienmarkierer Profi

Item no 68210 + Colour no

Technical data sheet

mipa

page 2 / 2 Professional Coating Systems



Drying times at 20 °C

Dust dry after approx.	10 min
Set to touch after approx.	30 min
Resistant after approx.	24 h
Overcoatable after approx.	24 h

Processing conditions From +10 °C and up to 60 % relative humidity. Ensure adequate air ventilation.

Storage Can be stored for 5 years in cool and dry places.

VOC-regulation EU limit value for the product (cat. B/e): 840 g/l
This product contains max. 800 g/l of VOC.

Safety information See safety data sheet

Processing instructions

Use our marking trolley (Markierungswagen Profi), the line marking applicator (Markierungsstock) or our marking pistol (Markierungspistole) for applying Mipa Linienmarkierer Profi.

Version: en 0126

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49 8703 92 20 · Fax: +49 8703 92 21 00 · mipa@mipa-paints.com · www.mipa-paints.com