Mipa Porenwischfiller

Technical data sheet

Intended use

1K filler to fill micropores by wiping the product on the surface, particularly of plastic.

Application mode:

Rub Mipa Porenwischfiller over the porous surface in a circular motion using a dry, clean and lint-free cloth pad. After drying (approx. 5-10 minutes at 20°C) remove any surplus material with a cloth moistened either with Mipa Kunststoffreiniger or Mipa Silikonentferner.


Spreading rate: --

Processing instructions



Colour

dark grey



Mixing ratio

Hardener	by weight (lacquer : hardener)	by volume (lacquer : hardener)
--	--	--



Hardener

for complete paintwork	for partial paintwork
--	--



Pot life

--



Thinner

--



Spray viscosity


ready for use

gravity spray gun	Airmix/Airless
--	--



Application mode

Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
--	--	--	--	--	--



Flash-off time

5 - 10 min

Dry coat thickness

--

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com



Drying time

object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
20 °C	--	--	--	--	30 min
60 °C	--	--	--	--	10 min

Note

Storage: at least 1 year in unopened original container

VOC Regulation : --

Processing conditions: from +10° C and up to 80 % relative air humidity. Ensure an adequate supply and exhaust air ventilation.

Processing instructions: The substrate must be clean, dry and free from grease. To be used only to fill micropores. Fill deep holes with Mipa polyester-based body fillers . Cleaning with Mipa Silikonentferner or Mipa Kunststoffreiniger is possible after 30 minutes after application.

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com